

# EZ 201



A4  
130ppm

RISO™... *The unique approach to printing*

## Accessories:



RISO EZ Drum A4



Card Feed Kit



RISO Auto Document Feeder AF-VI



RISO Key Card Counter IV:N



RISO Job Separator IV:N III

**Consumables:**  
**RISO MASTER eZ TYPE**  
 (295 sheets per roll)  
**RISO INK eZ TYPE**  
 (1,000ml per cartridge)

RISO PC Interface Card USB2.0  
 RISO Network Card  
 RISO Printer Driver for Macintosh  
 RISO Accounting Tool

## Specifications:

RISO EZ201	<b>Master-Making / Printing Methods</b>	High-speed digital master-making / Fully automatic stencil printing
	<b>Original Type</b>	Book, Sheet
	<b>Original Size</b>	When using the Glass Platen : 50 mm x 90 mm - 310 mm x 432 mm When using the AF-VI (option) : 100 mm x 148 mm - 310 mm x 432 mm
	<b>Original Paper Weight</b>	When using the Glass Platen : 10kg or less When using the AF-VI (option) : 50g/m <sup>2</sup> - 128g/m <sup>2</sup>
	<b>Scanning Area (max.)</b>	297 mm x 432 mm
	<b>Print Paper Size</b>	100 mm x 148 mm - 310 mm x 432 mm
	<b>Paper Supply Capacity</b>	1000 sheets (64 gsm)
	<b>Print Paper Weight</b>	Standard : 46 gsm - 157 gsm When using the Card Feed Kit (option): A4 and smaller size (100 gsm - 400 gsm) Legal and smaller size (100 gsm - 310 gsm) A3 and smaller size (100 gsm - 210 gsm)
	<b>Image Processing Mode</b>	Line, Photo, Duo, Pencil
	<b>Resolution</b>	Scanning resolution: 300dpi x 600dpi Print image resolution: 300dpi x 300dpi
	<b>Master-Making Time</b>	Approx. 25 seconds (for A4 / Landscape / 100% reproduction ratio)
	<b>Printing Area (max.)</b>	210 mm x 290 mm
	<b>Print Reproduction Ratio</b>	3 enlargements: 116%, 122%, 141% 3 reductions: 87%, 82%, 71% Margin+: 94%
	<b>Print Speed</b>	60 ppm - 130 ppm (5 steps variable)
	<b>Print Position Adjustment</b>	Vertical: ± 15 mm Horizontal: ± 10 mm
	<b>Ink Supply</b>	Fully automatic (1,000 ml per cartridge)
	<b>Master Supply / Disposal</b>	Fully automatic (295 sheets per roll)
	<b>Master Disposal Capacity</b>	Approx. 100 sheets
	<b>User Interface</b>	LED Panel with Progress Arrow indicators, Front Side Operation
	<b>Power Source</b>	EZ201E: 220V - 240V AC, <1.3A> 50Hz - 60Hz
<b>Dimensions (WxDxH) without Stand</b>	When in use: 1415mm(W) x 655mm(D) x 665mm(H) When in storage: 780mm(W) x 655mm(D) x 665mm(H)	
<b>Weight without Stand</b>	Approx. 100kg	

Specifications are subject to change without notice. Details may vary depending on the region.

## Alternative Power Solutions:

### RISO™ Power Pedestal

#### BACKUP CAPACITY

Keep printing, even when the power goes down!  
 This solution is perfect for areas with sporadic power issues, and can provide you with up to 2 days worth of printing without electricity.



### Risolar™

#### PRINT USING NATURAL ENERGY



This option allows the Risograph to run **entirely independent** of any mains connection. In this configuration, true off-the-grid printing is not only achievable, but simple to implement!

**AUTHORISED DISTRIBUTOR:**



RISO logo is the registered trademark of RISO KAGAKU CORPORATION.  
 RISO i Quality System and  are the trademarks of RISO KAGAKU CORPORATION.  
 Copyright ©2012 RISO KAGAKU CORPORATION. All rights reserved.  
 The colour of the actual product may vary from the colour shown in the brochure.

